

GREAT STUFF™

INSULATING FOAM SEALANT



NOW GREAT STUFF™ INSULATING FOAM IS EVEN GREATER!

GREAT STUFF™ Pestblock Insulating Foam Sealant

Features and Benefits:

- Fills, seals and insulates gaps up to 1" (25 mm)
- Use for up to 30 days with the SMART DISPENSER™
- Forms a long-lasting, airtight and water-resistant barrier
- Pale grey color bonds to most building materials and surfaces
- Tack-free in 5-15 minutes²
- Interior/exterior use³
- Blocks the entry of pests that can damage the house and its contents
- Contains no pesticides
- Helps improve the home's energy efficiency by sealing gaps and cracks
- UL Classified
- CCMC 13074-L
- ESR-1961

Block Pest Invasion:

- Spiders
- Ants
- Bees
- Cockroaches
- Other insects and critters



GREAT STUFF™ Pestblock Insulating Foam Sealant* is specifically designed to block insects and pests from entering the home by sealing gaps, cracks and holes where they commonly enter. This insulating foam sealant expands to fill, seal and insulate gaps up to 1" (25 mm), forming a long-lasting, airtight and water-resistant barrier. It blocks pests out of the home by eliminating points of entry.

In addition to blocking pests from the home, GREAT STUFF™ Pestblock Insulating Foam Sealant seals gaps and cracks to help keep air from leaking out of or seeping into the home's envelope. According to Residential Energy Services Network (RESNET) proper insulating and air sealing can help reduce energy costs by up to 30%.¹

Introducing the new patent-pending GREAT STUFF™ SMART DISPENSER™.

This next generation of foam sealant dispensing is a game-changer:

- **Reusable for up to 30 days;** now use it again and again!
- **No drip dispensing,** eliminates mess
- **Easy to use, greater control**
- Fill gaps efficiently and quickly
- Available only from GREAT STUFF™ Insulating Foams!

U.S. MADE

U.S. OWNED

GREAT STUFF™ SMART DISPENSER™
USE IT AGAIN AND AGAIN!



Where to Use GREAT STUFF™ Pestblock



PVC Pipe Penetration



Electrical Cable Lines



Water Faucet Penetration



Attic Hatch Frame



Rim Joists



Sill Plate



Plumbing Penetration

Meet the GREAT STUFF™ Foam Sealant Family:

Our line of foam sealants are a simple-to-use, cost-effective money-saving solution for any DIYer.

- **GREAT STUFF™ Gaps & Cracks*** — Fills, seals and insulates gaps up to 1 inch.
- **GREAT STUFF™ Window & Door*** — Seals airtight to insulate and reduce drafts, drip-free. When applied properly, won't distort or bow window and door frames.
- **GREAT STUFF™ Fireblock*** — Seals to impede fire and smoke with less mess.**
- **GREAT STUFF™ Big Gap Filler*** — Seals gaps up to 3 inches with less mess.
- **GREAT STUFF™ Pestblock*** — Blocks out ants, roaches, spiders, bees and more with no pesticides.
- **GREAT STUFF™ Multipurpose Black*** — Fills, seals and insulates indoor and outdoor gaps up to 1 inch.
- **GREAT STUFF™ Pond & Stone*** — Directs water flow with fish-safe adhesive and sealant.



¹ Source: www.energystar.gov

² Actual cure time will depend on temperature, relative humidity and size of foam bead.

³ Skin of cured foam can discolor if exposed to natural light; paint or coat foam for best results.

* Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

**Intended for use in residential application to maintain the continuity of an approved fire block material.

In the United States

The Dow Chemical Company
Performance Building Solutions
 200 Larkin Center
 Midland, MI 48674

In Canada

Dow Chemical Canada ULC
Performance Building Solutions
 450 – 1st St. SW
 Suite 2100
 Calgary, AB T2P 5H1

For Technical Information:

1-866-583-BLUE (2583) (English)
1-800-363-6210 (French)

greatstuff.dupont.com

For Sales Information:

1-800-232-2436 (English)
1-800-565-1255 (French)

NOTICE: No freedom from any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries or regions. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DOW. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release The Dow Chemical Company, and its subsidiaries, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

Dow Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheets ((M)SDS), call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood burning stoves, gas stoves and gas dryers are properly vented to the outside. See website: <http://www.epa.gov/iaq/homes/hipventilation.html>. In Canada visit: <http://archive.nrc-cnrc.gc.ca/eng/ibp/irc/bsi/83-house-ventilation.html>.

GREAT STUFF™ Insulating Foam sealant and adhesive products contain isocyanate and a flammable blowing agent. Read all instructions and (Material) Safety Data Sheet ((M)SDS), carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and safety glasses or goggles. Not for use in aviation, or food/beverage contact, or as structural support in marine applications. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as behind walls and under tub surrounds; improper use of the product could result in the accumulation of flammable vapors and/or uncured material. Failure to follow the warnings and instructions provided with the product, and/or all applicable rules and regulations, can result in injury or death.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

©™Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.

Printed in the U.S.A.

Form No. 43-D100015-enNA-0918 BBI